



Dinils Adhesives Pvt. Ltd.
30, 7th Floor, Tardeo AC Market,
Tardeo Road, Mumbai 400 034
Tel: 91-22-23514261/63 **Fax:** 91-22-23514297
E-Mail: info@dinils.com **Web Site:** www.dinils.com
CIN: U99999MH1965PTC013108

TECHNICAL DATA SHEET

BOND FAST SR 888 (Synthetic Rubber Adhesive)

Base	: Blend of synthetic rubber and synthetic resins in organic solvents
Colour	: Light Yellow
End Use	: Decorative Laminates to Plywood, PVC/Cork to Metal, AC Ducting Bus Body Building, Automobiles, Carpets, PVC Vinyl Floorings etc.
Solid Content	: 23% [\pm 2%]
Viscosity at 30°C	: 1300 CPS (\pm 100 CPS)
Curing Time	: 1-2 hours, final curing 24 hours
Ageing Stability	: Outstanding degree of resistance to high heat / temperature, oxidation, water, chemicals, acids etc.
Shelf Life	: 1 year, depending on climatic conditions
Application	: Stir well before use * Surfaces to be bonded must be clean, dry, free from dust, oil etc. * Both surfaces to be bonded should be thin coated with the adhesive * Allow this to DRY until the adhesive film can be touched without lifting i.e. TOUCH DRY in about 5 to 10 minutes before final assembly * Press the surfaces together over the whole area to ensure overall contact * Bonded surfaces can be handled within 1 hour for further processing and may be used for normal service after 24 hours
Safety	: INFLAMMABLE! Ensure that the lids are secured during storage. Avoid heat and ignition sources. Handle in a well ventilated area. To be stored in a cool dry place.
Packing	: 25l, 5l, 100 mls

DISCLAIMER

ALL INFORMATION IS GIVEN IN GOOD FAITH, BASED ON OUR RESEARCH AND EXPERIENCE BUT WITHOUT WARRANTY. WE ADVISE CUSTOMERS TO CARRY OUT THEIR OWN TESTS TO ENSURE THAT THE MATERIAL IS SUITABLE FOR THEIR OWN PARTICULAR REQUIREMENTS.